

ZA14JE

ELECTRIC ARTICULATING BOOM LIFTS

Comply with CE/ANSI/GB Standard

HIGHLIGHTS

- Center layout, great structural rigidity, and small boom deflection.
- Advanced dual control system (valve control + pump control) offers a energy-saving and smooth control.
- Accurate and efficient traveling AC drive system provides strong power and stable control.

FEATURES

Standard Features

Proportional controls

All motion alarm

Flashing amber beacon

Self-closing entry gate

Emergency descent system

Emergency stop button

Auto-leveling system

On-board diagnostic system

Over tilt protection system

Drivable at full height

Load sensing system

4.3' LED display

Horn

Accessories & Options

AC power to platform

Airline to platform

Non-marking tire



ZOOMLION

ELECTRIC ARTICULATING BOOM LIFTS

Comply with CE/ANSI/GB Standard

	Model	ZA14JE
SIZE	Work Height	16m
	Platform Height	14m
	Horizontal Outreach	7.50m
	Up and Over Height	7.74m
	A - Stowed Length	6.6m
	B - Stowed Width	1.75m
	C - Stowed Height	2m
	D - Platform Length	1.52m
	E - Platform Width	0.76m
	F - Wheelbase	2.05m
G - Ground Clearance	200mm	
PERFORMANCE	Platform Capacity	230kg
	Drive Speed	6.1km/h
	Gradeability	30%(17°)
	Axles Oscillation	
	Turning Radius (Inside)	0.79m
	Turning Radius (Outside)	3.15m
	Swing	360° continuous
	Platform Rotation	±90°
	H-Tail Swing	0m
	Max. Working Slope	2/4°
Max. Wind Speed	12.5m/s	
POWER	Battery	8x6V/420Ah
	Charger	48V/60A
	Drive Motor	AC 32V/3.3kw
	Lift Motor	DC 48V/5kw
	Auxiliary Power	Manual Pump
	Hydraulic Tank Capacity	30L
TIRE	Type	17.5x6.75 Foam-filled Tires
WEIGHT	Gross	6800kg

Range of motion ZA14J

